



Tel : 603-42949749
 Fax : 603-42949759
www.lpotech.com.my

LP MATERIAL HANDLING SYSTEM



APPLICATION:

- Production Planning & Control.
- Production Status.
- JIT (Just In Time) Material Handing to reduce work space

BENEFIT:

- Promotes Healthy Team (Line) Competition or Awareness.
- Indicates Corrective Action Needs.
- Real Time Production Material Information for supervisor & Manager.
- Reduction Of Paperwork.
- Increase revenue

FEATURES:

- Large & Accurate Led Display .
- Super Bright Led.
- Low Maintenance.

Specification

No. of Row	3
Digits Height	2.3", 4", 6", and 8"
Viewing Distance	2.3" Solid Segment - 60' / 80'
Recomented / Maximum	4" Solid Segment - 100' / 140' 6" Discrete - 180' / 240' 8" Discrete - 240' / 320'
Digits	2, 3, 4, 5, 6
Sided of Display	Single Sided or Double Sided
Power Source	240VAC or 110VAC + 10% 50 Hz
Memory	Non-volatile memory
Mounting	Hang or wall Type
Call Methode	Using Individual Calling keypad
Output	Buzzer and Light
Reset	Remote Reset
Setting	Infrared Remote control up to 20 feet
Communication	Rs485


Double Sided	Dimension (mm) ± 10%			
Model	Led Height	Length	Width	Height
LPM-42-DRG	4"	510	124	539

HOW TO ORDER

LPM-AB-CD

Key	Description	Choices
A	Digits Height	2= 2.3" (Solid Digits) 4= 4" (Solid Digits) 6= 6" (Discrete Digits) 8= 8" (Discrete Digits)
B	Number of digits	2, 3, 4, 5, 6
C	Sided of display	D : Double sided S : Single Sided
D	Display Color	No [RED (Standard) G= Green A= Amber (Discrete only)

Keypad



We also provide customer with solutions and a variety of customize products Which meet your requirements economically.

Please Feel Free to contact us if you have any doubt?