

LP Single Row Digital Counter



BENEFIT:

- : Promotes Healthy Team (Line) Competition or Awareness
- : Indicates Corrective Action Needs.
- : Motivate Staff & Improve Productivity.
- : Real Time Production Information for supervisor & Manager.

FEATURES:

- : Large & Accurate Super Bright Led Display .
- : Low Maintenance

APPLICATION:

- : Production Planning & Control.
- : Production Status.

Specification

No. of Row	1
Digits Height	1 ", 2.3", 4", 6", 8" and Others
Viewing Distance	2.24" Solid Segment – 14 meter
Recomented / Maximum	4" Solid Segment – 25 meter 6" Discrete – 38 meter 8" Discrete - 50 meter
Digits	2, 3, 4, 5, 6
Sided of Display	Single Sided or Double Sided
Power Source	100 -240VAC $\pm$ 10% , 0.5A ,50 - 60 Hz (12V 1.5A Ac to Dc Adaptor)
Memory	Eeprom
Mounting	Hang or wall Type
Count Input	a - Edge Trigger NPN or PNP b - Relay, Microswitch etc.
Reset	Remote Reset
Option	Relay Output

HOW TO ORDER PRODUCTION COUNTER

LP-C-1AB-C-D-E

Key	Description	Choices
A	Digits Height	1= 1" (Solid Digits) 2= 2.3" (Solid Digits) 4= 4" (Solid Digits) 6= 6" (Discrete Digits) 8= 8" (Discrete Digits) O= Others
B	Number of digits	2, 3, 4, 5, 6
C	Sided of display	DR : Double sided SR : Single Sided
D	Display Colour	RED (Standard) G= Green A= Amber (Discrete only)
E	Relay Output	O



Double Sided Display

We also provide customer with solutions and a variety of customize products
Which meet your requirements economically.

Please Feel Free to contact us if you have any doubt?

LP Single Row Digital Counter



Specification

Model	LP-C-143-DR	LP-C-144-DR	LP-C-145-DR	LP-C-146-DR	LP-C-143-SR	LP-C-144-SR	LP-C-145-SR	LP-C-146-SR	LP-C-123-DR	LP-C-124-DR	LP-C-125-DR	LP-C-126-DR	LP-C-123-SR	LP-C-124-SR	LP-C-125-SR	LP-C-126-SR
Display	Indoor Display															
No of row	1															
Segment	Solid 7 Segment Display															
Figure size	4 inch								2.24 inch							
Digits	3	4	5	6	3	4	5	6	3	4	5	6	3	4	5	6
Color of LED	Red															
Sided of display	Double Sided				Single Sided				Double Sided				Single Sided			
Count and Reset Input	Non Contact : Open Collector (NPN) or 24V (PNP)															
	Contact : Relay, microswitch, etc															
Sensor Power	12vdc 100mA															
Memory	EEPROM															
Visibility	4'' up to 25 Meter								2.3" up to 14 Meter							
Power source	100 -240VAC $\pm$ 10% , 0.5A ,50 - 60 Hz															
Mounting	Hang type or Wall Mould Type															
Dimension $\pm$ 1mm Unit = mm	H195xW350xD76	H195xW430xD76	H195xW525xD76	H195xW615xD77	H180xW400xD49	H180xW490xD49	H180xW580XD49	H179xW670XD50	H146XW220XD76	H146XW270XD76	H146XW316XD76	H146XW365XD77	H127XW220XD49	H127XW254XD49	H127XW300XD49	H127XW362XD50

Option

Photoelectric sensors

Press Button Switch

