

LP Room Temperature & Humidity Display



BENEFIT:

- : Ensure Proper Indoor Humidity has importance skin ,allergen and other health benefits
- : Environmental Monitoring

: FEATURES:

- : Large & Accurate Super Bright Led Display .
- : Low Maintenance

: APPLICATION:

- : Clean room and Warehouse
- : Hospital
- : Server Room

Specification

No. of Row	1 or 2
Digits Height	2.24", 4", 6", 8" and Others
Viewing Distance	2.24" Solid Segment – 14 Meter
Recomented / Maximum	4" Solid Segment – 25 meter 6" Discrete – 38 meter 8" Discrete – 50 meter
Digits	2, or 3
Sided of Display	Single Sided or Double Sided
Power Source	240VAC or 110VAC $\pm$ 10% 50 Hz
Mounting	Hang or wall Type

Display Value

Temperature (3 digits)	0 °C ~ 60°C
Humidity (2 digits)	0%RH ~ 99%RH
Accuracy	0 °C ~ 60.0°C +- 1°C @25°C 20%RH ~ 80%RH +- 4% @25°C

Display Value

Temperature (3 digits)	0 °C ~ 60.0°C
Humidity (3 digits)	0.0%RH ~ 99.9%RH
Accuracy	0 °C ~ 60.0°C 20.0%RH ~ 80.0%RH +- 4% @25°C

HOW TO ORDER TEMPERATURE AND HUMIDITY DISPLAY

LPTH-ABC-D-E-F

	Description	Choices
A	Row	1 2
B	Digits Height	2= 2.24" (Solid Digits) 4= 4" (Solid Digits) 6= 6" (Discrete Digits) 8= 8" (Discrete Digits) O= Others
C	Number of digits	2 = 2 Digits 3 = 3 Digits 3A = 2 & 3 Digits
D	Sided of display	DR : Double sided SR : Single Sided
E	Display Colour	R= RED (Standard) G= Green A= Amber (Discrete only)
F	Cable length	

- | | |
|----------|-----------------------|
| Standard | 1= 5 meter |
| | 2= 10 meter |
| | 3= More then 10 Meter |

We also provide customer with solutions and a variety of customize Products which meet your requirements economically.
Please Feel Free to contact us if you have any doubt?

Tel : 603-42949749

Fax : 603-42949759

www.lptech.com.my

LP Room Temperature & Humidity Display



Specification

Model	LPTH-143-DR	LPTH-2432-DR	LPTH-243-DR	LPTH-143-SR	LPTH-2432-SR	LPTH-243-SR	LPTH-123-DR	LPTH-2232-DR	LPTH-223-DR	LPTH-123-SR	LPTH-2232-SR	LPTH-23-SR
Display	Indoor display											
No of row	1	2	2	1	2	2	1	2	2	1	2	2
Segment	Solid 7 Segment Display											
Figure size	4"						2.24"					
Color of LED	Standard RED											
Sensor cable length	Standard 5 meter for 2 Row display											
Sided of display	Double Sided			Single Sided			Double Sided			Single Sided		
Digits	3 Digits Temperature	3 Digits Temperature & 2 Digits Humidity	3 Digits Temperature & 3 Digits Humidity	3 Digits Temperature	3 Digits Temperature & 2 Digits Humidity	3 Digits Temperature & 3 Digits Humidity	3 Digits Temperature	3 Digits Temperature & 2 Digits Humidity	3 Digits Temperature & 3 Digits Humidity	3 Digits Temperature	3 Digits Temperature & 2 Digits Humidity	3 Digits Temperature & 3 Digits Humidity
Display Format	Temperature : 0 °C ~60.0 °C											
	Humidity : 0 % ~ 99 %RH Or 0% ~ 99.9%RH											
Accuracy	0°C ~ 60.0°C ± 1°C @25°C											
	20% ~ 80% ± 4% @ 25°C											
Visibility	2.24" Up To 14 Meter and 4" Up To 25 Meter											
Power source	100 -240VAC ± 10%											
Mounting	Hang Type Mound			Wall Mound			Hang Type Mound			Wall Mound		
Dimension ± 5mm Unit = mm	W500 X H195 XD76	W500 X H372 XD76	W500 X H372 XD76	W471 X H179 XD49	W471 X H350 XD49	W471 X H350 XD49	W355 X H146 XD76	W355 X H264 XD76	W355 X H246 XD76	W245 X H124 X D49	W330 X H240 X D49	W330 X H240 X D49

We also provide customer with solution and a variety of customize product which meet their requirement economically