

LP 3 Row Digital Counter



BENEFIT:

- : Promotes Healthy Team (Line) Competition or Awareness
- : Indicates Corrective Action Needs.
- : Motivate Staff & Improve Productivity.
- : Real Time Production Information for supervisor & Manager.

FEATURES:

- : Large & Accurate Super Bright Led Display .
- : Low Maintenance

APPLICATION:

- : Production Planning & Control.
- : Production Status.

Specification

No. of Row	3
Digits Height	2.24", 4", 6", 8" and Others
Viewing Distance	2.24" Solid Segment – 14 meter
Recomented / Maximum	4" Solid Segment – 25 meter 6" Discrete – 38 meter 8" Discrete - 50 meter
Digits	2, 3, 4, 5, 6
Sided of Display	Single Sided or Double Sided
Power Source	240VAC or 110VAC $\pm$ 10% 50 Hz
Memory	EEPROM
Mounting	Hang or wall Type
Count Input	a - Edge Trigger NPN or PNP b - Relay, Microswitch etc.
Reset	Remote Reset
Setting	Infrared Remote control up to 20 feet
Option 1	RS232, Rs485 Communication
Option 2	Break Time Setting

HOW TO ORDER PRODUCTION COUNTER

LP-C-3AB-C-D-E

Key	Description	Choices
A	Digits Height	1.2 = 1.2" (Solid Digits) 2 = 2.3" (Solid Digits) 4 = 4" (Solid Digits) 6 = 6" (Discrete Digits) 8 = 8" (Discrete Digits) 0 = Others
B	Number of digits	2, 3, 4, 5, 6
C	Sided of display	D : Double sided S : Single Sided
D	Display Colour	R= RED G= Green A= Amber (Discrete only)
E	Line Description	1=TARGET 2=PLAN 3=ACTUAL 4=DIFFERENCE 5=OTHERS

**We also provide customer with solutions and a variety of customize products
Which meet your requirements economically.**

Refer Next Page for more information

LP 3 Row Digital Counter



Specification

Model	LP-C-343-DR-D-E	LP-C-344-DR-D-E	LP-C-345-DR-D-E	LP-C-343-SR-D-E	LP-C-344-SR-D-E	LP-C-345-SR-D-E	LP-C-323-DR-D-E	LP-C-324-DR-D-E	LP-C-325-DR-D-E	LP-C-323-SR-D-E	LP-C-324-SR-D-E	LP-C-325-SR-D-E
Display	Indoor Display											
No of row	3											
Segment	Solid 7 Segment Display											
Figure size	4 inch						2.3 inch					
Digits	3	4	5	3	4	5	3	4	5	3	4	5
Color of LED	Red											
Sided of display	Double Sided			Single Sided			Double Sided			Single Sided		
Count and Reset Input	Non Contact : Open Collector (NPN Sensor)											
	Contact : Relay, microswitch, etc											
Sensor Power	12vdc 100mA											
Memory	EEPROM											
Visibility	4'' up to 50 Meter						2.3" up to 25 Meter					
Power source	100 -240VAC $\pm$ 10% , 0.5A ,50 - 60 Hz											
Mounting	Hang type or Wall Mould Type											
Dimension $\pm$ 5mm Unit = mm	H520xW590xD76	H520xW680xD76	H520xW770xD76	H498xW564xD49	H498xW654xD49	H498xW744xD49	H350xW378XD76	H350xW425XD76	H350xW472XD76	H338xW367XD49	H338xW414XD49	H338xW461XD49

Note : Please Specified the Line Description before ordering

