



Tel : 603-42949749
Fax : 603-42949759
www.lptech.com.my

Release : 07/17
Drawing Name : LP Analogue display-D7

LP Analog Digital Display



BENEFIT:

- : Promotes Healthy Team (Line) Competition or Awareness
- : Indicates Corrective Action Needs.
- : Motivate Staff & Improve Productivity.
- : Real Time Production Information for supervisor & Manager.

FEATURES:

- : Large & Accurate Super Bright Led Display .
- : Low Maintenance

APPLICATION:

- : Production Planning & Control.
- : Production Status.
- : Super Bright Led.

Specification

No. of Row	1 OR 2
Digits Height	2.3", 4", 6", 8" and Others
Viewing Distance	2.24" Solid Segment – 14 meter
Recomented / Maximum	4" Solid Segment – 25 meter 6" Discrete – 38 meter 8" Discrete - 50 meter
Digits	2, 3 and 4
Sided of Display	Single Sided or Double Sided
Input Current	0 -20mA, 4 - 20mA
Input Voltage	0 – 5v, 0 – 10V
Power Source	240VAC or 110VAC $\pm$ 10% 50 Hz
Mounting	Hang or wall Type



HOW TO ORDER

LP-A-BCD-E-F-G

Key	Description	Choices
B	ROW	1 = 1 ROW 2 = 2 ROW
C	Digits Height	2= 2.3" (Solid Digits) 4= 4" (Solid Digits) 6= 6" (Discrete Digits) 8= 8" (Discrete Digits) O= Others
D	Number of digits	2, 3, and 4
E	Sided of display	DS : Double sided SS : Single Sided
F	Display Colour	RED (Standard) G = Green A = Amber (Discrete only)
G	Input	A =4-20mA V = 0-10v

We also provide customer with solutions and a variety of customize products
Which meet your requirements economically.

Please Feel Free to contact us if you have any doubt?

LP Single Row 4-20mA Digital Display



Specification

Model	LP-A-143-DR	LP-A-144-DR	LP-A-145-DR	LP-A-143-SR	LP-A-144-SR	LP-A-145-SR	LP-A-123-DR	LP-A-124-DR	LP-A-125-DR	LP-A-123-SR	LP-A-124-SR	LP-A-125-SR
Display	Indoor Display											
No of row	1											
Segment	Solid 7 Segment Display											
Figure size	4 inch						2.3 inch					
Digits	3	4	5	3	4	5	3	4	5	3	4	5
Color of LED	Red											
Sided of display	Double Sided			Single Sided			Double Sided			Single Sided		
Input	4-20mA											
Setting	Remote controller up to 20 feet											
Visibility	4” up to 50 Meter						2.3" up to 25 Meter					
Power source	100 -240VAC ± 10% , 0.5A ,50 - 60 Hz											
Mounting	Hang type or Wall Mould Type											
Dimension ±5mm Unit = mm	H195xW350xD76	H195xW430xD76	H195xW525xD76	H179xW 326xD49	H179xW412xD49	H179xW510xD49	H146xW220xD76	H146xW270xD76	H146xW316xD76	H124xW220xD49	H124xW246xD49	H124xW300xD49

We Also Provide Customer With Solutions And A Variety Of Customize Product Which Meet Their Requirement Economically.

Tel : 603-42949749

Fax : 603-42949759

www.lptech.com.my

LP 2 Row 4-20mA Digital Display



Specification

Model	LP-A-244-SR-4-20mA
Display	Indoor Display
No of row	2
Segment	Solid 7 Segment Display
Figure size	4 "
Digits	4
Color of LED	Red
Sided of display	Single Sided
Input	2 x 4-20mA
Visibility	50 METER
Power source	100 -240VAC $\pm$ 10% , 0.5A ,50 - 60 Hz
Mounting	Hang type or Wall Mount
Dimension $\pm$ 5mm Unit = mm	W577 x H327 x D49

We Also Provide Customer With Solutions And A Variety Of Customize Product Which Meet Their Requirement Economically.